


## Poldina mini \_Table lamp



Cordless, rechargeable, battery table lamp. A touch control on the top of the lamp head allows you to switch the light on, adjust its intensity and select its color temperature. And thanks to its high IP rating, the lamp can also be used outdoors (except for models with a metallic-leaf or galvanized finish which are not recommended for continuous outdoor use). An electronic control system monitors and indicates the remaining battery power to ensure recharging is optimized and always performed correctly. The lamp comes with a contact charging base. USB charger included. The lamp can be customized with a ceramic cover that can be purchased separately.

Ø 11 cm  
Ø 4,3 in













10 x 10 cm  
3,9 x 3,9 in



LED dimmable IP65

### LD0320

	White	<b>B3</b>		Silver color leaf	<b>BFA</b>
				Not suitable for outdoor use	
	Corten	<b>R3</b>		Dark gray	<b>N3</b>
	Sand	<b>S3</b>		Gold color leaf	<b>BFO</b>
				Not suitable for outdoor use	
	Copper color leaf	<b>RFR</b>		Glossy gold	<b>O3</b>
	Not suitable for outdoor use			Not suitable for outdoor use	
	Glossy chrome	<b>C3</b>			
	Not suitable for outdoor use				



DESIGN IN ITALY BY ZAFFERANO SRL, MADE IN PRC

Zafferano SRL - Viale dell'Industria, 26 31055 Quinto di Treviso - Italy [www.zafferanoitalia.com](http://www.zafferanoitalia.com)

# Poldina mini \_Table lamp

## Lighting specifications

source	LED
type	SMD
total power	2.2 W
power LED	2.0 W
color temperature	2200 - 2700 - 3000 K
lumen lamp	185 - 199 - 203 lm
lumen LED	234 - 251 - 256 lm
beam angle	45°
CRI	> 80
class	F
dimmer	TOUCH DIMMER
motion sensor	NO

## Electrical specifications

classe	3
supply voltage	5Vdc max.1A
battery	2 cell li-ion battery pack mod. 18650 3,7v - 2200 ma/h
battery life	12 H.
charging time	6/7 H.
driver input	100-240V
driver frequency	50/60 Hz

## ACCESSORIES

### LD0340RA




6 cm • 13.5 cm • 4.5 cm • 2.2 W  
• IP20 • 100-240V • 50/60 Hz




Black

### LD0350RB




9.4 cm • 9.4 cm • IP20 • 100-240V  
• 50/60 Hz




Black

### LD0350RP



33 cm • 51 cm • 5.8 cm • 2.2 W  
• IP20 • 100-240V • 50/60 Hz



Black

### LD0350



Ø 13 cm • 10 cm • 50/60 Hz

09